

*If you are using a printed copy of this procedure, and not the on-screen version, then you **MUST** make sure the dates at the bottom of the printed copy and the on-screen version match. The on-screen version of the Collider-Accelerator Department Procedure is the Official Version. Hard copies of all signed, official, C-A Operating Procedures are kept on file in the C-A ESHQ Training Office, Bldg. 911A.*

C-A OPERATIONS PROCEDURES MANUAL

ATTACHMENT

8.13.a C-A Radiation Storage Area

Text Page 2

C-A OPM Procedures in which this Attachment is used.		
8.13		

Hand Processed Changes

<u>HPC No.</u>	<u>Date</u>	<u>Page Nos.</u>	<u>Initials</u>
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Approved: _____ *Signature on File* _____
 Collider-Accelerator Department Chairman Date

P. Cirnigliaro

C-A RADIATION STORAGE AREA

The C-A Department Radiation Storage Area is located on the west side of the target building. The area is to be available to all groups within the C-A Department. Available outside Building 912 is a fenced and locked storage area.

Any material to be stored must be in useable condition, or there should be plans to make it useable within a two year period. Any piece of radioactive equipment, not to be used or repaired in a two year period, shall be properly disposed of. Refer to BNL Radiological Controls Manual.

The Radiation Storage Area shall not be used to store scrap.

Due to space limitations, the average radiation level on any piece of equipment to be stored in the Radiation Storage Area shall initially not be less than average of 30 mr/hr@ 12 inches. The individual groups shall store equipment with radiation levels less than average. All requests shall include a sketch of the equipment to be stored, with current radiation levels at twelve inches. If the equipment is determined to be contaminated (over 1000 DPM/Smear removable), the owner shall either have it decontaminated or sealed in plastic.

When a piece of equipment has been in storage for longer than two years, it shall be reviewed for the following:

- If the average radiation level has dropped below 30mr/hr @ 12 inch, the equipment shall be returned to the appropriate group for storage.
- Any damaged, obsolete, or unusable equipment shall be looked at, with a view towards its ultimate disposal by its owner.